

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 January 2004 (29.01.2004)

PCT

(10) International Publication Number
WO 2004/009957 A1

(51) International Patent Classification⁷: **E21B 47/06,**
G01L 19/04

(21) International Application Number:
PCT/US2002/023272

(22) International Filing Date: 23 July 2002 (23.07.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **HAL-
LIBURTON ENERGY SERVICES, INC.** [US/US];
2601 Beltline Road, Carrollton, TX 75006 (US).

(71) Applicant (for US only): **DENNIS, John, R.** [US/US];
2514 Valhalla Court, Bozeman, MT 59715 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SKINNER, Neal,**
G. [US/US]; 1219 Indian Paint, Lewisville, TX 75076


(US). **LEBLANC, Michel** [CA/US]; 3051 Trevor House
Drive, Unit C, Oakton, VA 22124 (US). **JOHNSON,**
Gregg [US/US]; 5209 Noyes Court, Fairfax, VA 22032
(US). **TODD, Michael, D.** [US/US]; 402 South Whiting
Street #304, Alexandria, VA 22304 (US).

(74) Agent: **SMITH, Marlin, R.**; Konneker & Smith, P.C.,
Suite 230, 660 North Central Expressway, Plano, TX 75074
(US).

(81) Designated States (*national*): AE, AG, AL, AM, AT (util-
ity model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA,
CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (util-
ity model), DE, DK (utility model), DK, DM, DZ, EC, EE
(utility model), EE, ES, FI (utility model), FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ,
LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI,
SK (utility model), SK, SL, TJ, TM, TR, TT, TZ, UA, UG,
US, UZ, VN, YU, ZA, ZW.

[Continued on next page]

(54) Title: SUBTERRANEAN WELL PRESSURE AND TEMPERATURE MEASUREMENT



(57) Abstract: A well pressure and temperature measurement system and method are provided. In a described embodiment, a sensor system (12) includes multiple strain sensors attached to a structure which changes dimensionally in response to well pressure and temperature changes. The strain sensors may be fiber optic sensors. The structure may be tubular and the strain sensors may detect axial and hoop strains in the structure.

WO 2004/009957 A1



(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

5

SUBTERRANEAN WELL PRESSURE AND TEMPERATURE MEASUREMENT

10

TECHNICAL FIELD

The present invention relates generally to operations performed and
15 equipment utilized in conjunction with a subterranean well and, in an
embodiment described herein, more particularly provides pressure and
temperature measurement in such wells.

BACKGROUND

20

Pressure and temperature measurement in wells has generally been
accomplished using pressure and temperature transducers which utilize separate
pressure and temperature sensors. For example, a transducer may include a
piezoelectric pressure sensor and a thermocouple temperature sensor.

25 Unfortunately, however, most methods of measuring pressure are
sensitive to changes in temperature. If the temperature changes relatively
rapidly, as happens many times during typical well operations, such as drill stem
testing, gravel packing, etc., then it may be very difficult to accurately measure

pressure in the well. For example, for the transducer described above, the thermocouple and the piezoelectric crystal may have different temperature change response rates and/or may be located in different positions in the transducer, so that the temperature indicated by the thermocouple is not
5 necessarily the temperature of the piezoelectric crystal.

Therefore, it would be highly desirable to provide a method of measuring pressure in a well in which accuracy of the measurement is improved. The ability to eliminate the contribution of temperature change to the pressure measurement would be very advantageous.

10

SUMMARY

In carrying out the principles of the present invention, in accordance with an embodiment thereof, a sensor system is provided. The sensor system is an
15 advance in the art in that it eliminates one or more problems in prior sensor systems, and/or performs more efficiently than prior systems.

Methods of measuring pressure in a well are also provided by the present invention. In one example, a pressure measuring method includes the steps of applying a pressure differential across a structure positioned in a well, and
20 applying a temperature change to the structure. A strain in the structure induced by the pressure differential and the temperature change is detected using one sensor. A different strain, also induced by the pressure differential and the temperature change, is detected using another sensor.

A predetermined mathematical relationship exists between the pressure
25 differential and the strains. Therefore, the pressure differential may be readily known when the first and second strains are known. In this example, the strains detected by the sensors may each include the same contribution due to strain induced by the temperature change in the structure.

In another example of a method of measuring pressure in a well provided
30 by the invention, the method includes the steps of applying a pressure differential and a temperature change to a structure positioned in a well, detecting a strain in

the structure induced by the pressure differential and the temperature change using one sensor, and detecting another strain in the structure induced by the temperature change using another strain sensor.

5 The latter strain sensor does not detect strain induced in the structure by the pressure differential. However, a predetermined mathematical relationship does exist between the pressure differential and the strains. In this example, the difference between the strains equals the strain induced in the structure by the pressure differential, since each of the strains includes the same contribution due to the temperature change.

10 In yet another method of measuring pressure in a well, the method includes the steps of applying a pressure differential across a structure positioned in the well, detecting a strain in the structure in one direction using a strain sensor, detecting a different strain in the structure in another direction using another strain sensor, and calculating the pressure differential using a
15 predetermined mathematical relationship between the pressure differential and the strains.

Specific examples are described below of various sensor systems provided by the invention. In one example, a sensor system includes a structure having multiple portions. A pressure differential is applied across one portion, the
20 pressure differential existing between surfaces formed on the portion.

Strain sensors detect strain in the structure induced by a temperature change in the well. One strain sensor detects strain in the one portion induced by the pressure differential. Another strain sensor detects strain in another portion of the structure due to the temperature change, but does not detect strain in the
25 other portion induced by the pressure differential.

In another example, a sensor system is described which includes a structure having a pressure differential applied across a membrane of the structure. The pressure differential exists between well pressure applied to one side of the membrane and another pressure applied to another side of the
30 membrane. Strain sensors detect strain in the membrane induced by the pressure differential and by a temperature change in the well. One strain sensor

detects strain in the membrane in a first direction, and the other strain sensor detects strain in the membrane in a second direction.

In still another example, a sensor system is provided which includes a tubular structure having a pressure differential applied across its inner and outer surfaces. The pressure differential exists between well pressure applied to one of the inner and outer surfaces and another pressure applied to the other of the inner and outer surfaces. Strain sensors detect strain in the structure induced by the pressure differential and by a temperature change in the well. One strain sensor detects strain in the structure in a first direction, and another strain sensor detects strain in the structure in a second direction.

In a further example of a sensor system provided by the invention, the sensor system includes a structure in which strain is induced in response to a pressure differential in a well and strain sensors attached to the structure and detecting strain in the structure when the pressure differential exists in the well. One strain sensor detects a strain in a direction in the structure, and another strain sensor detects another strain in another direction in the structure.

In each of the above examples, at least one of the strain sensors may be a fiber optic sensor. The fiber optic sensor may comprise an interferometer or fiber grating. Any of a wide variety of fiber optic sensors may be used.

These and other features, advantages, benefits and objects of the present invention will become apparent to one of ordinary skill in the art upon careful consideration of the detailed description of representative embodiments of the invention hereinbelow and the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic view of a method embodying principles of the present invention;

FIG. 2 is a schematic cross-sectional view of a sensor system embodying principles of the invention;

FIG. 3 is a graph representative of reflectivity vs. wavelength for fiber optic sensors of the sensor system of FIG. 2;

FIG. 4 is a schematic cross-sectional view of a second sensor system embodying principles of the invention;

5 FIG. 5 is a cross-sectional view of the second sensor system, taken along line 5-5 of FIG. 4; and

FIG. 6 is a schematic cross-sectional view of a third sensor system embodying principles of the invention.

10

DETAILED DESCRIPTION

Representatively illustrated in FIG. 1 is a method 10 which embodies principles of the present invention. In the following description of the method 10 and other apparatus and methods described herein, directional terms, such as
15 “above”, “below”, “upper”, “lower”, etc., are used only for convenience in referring to the accompanying drawings. Additionally, it is to be understood that the various embodiments of the present invention described herein may be utilized in various orientations, such as inclined, inverted, horizontal, vertical, etc., and in various configurations, without departing from the principles of the present
20 invention.

In the method 10, a sensor system 12 is positioned in a well for measuring pressure and temperature during operations in the well. As depicted in FIG. 1, the sensor system 12 is conveyed into the well attached to an item of equipment 14, such as a drill stem testing tool. However, it is to be clearly understood that
25 the sensor system 12 may be otherwise positioned in the well, and may be used in well operations other than drill stem testing, in other methods embodying principles of the invention.

Lines 16 extend from the sensor system 12 to surface data acquisition equipment 18. The lines 16 may be any type of data transmission lines, such as
30 electrical lines, fiber optic lines, hydraulic lines, etc., and the lines may also perform other functions, such as power source, control, etc. Alternatively, data

transmission and any of the other functions of the lines 16 may be provided by wireless means, such electromagnetic, acoustic, pressure pulse or other type of telemetry.

Preferably, the sensor system 12 includes one or more fiber optic sensors, and so the lines 16 in the method 10 may conveniently be fiber optic lines extending into the well between the sensor system and the data acquisition equipment 18. In that case, the equipment 18 could include the appropriate means for optical communication, such as one or more lasers, photoelectric detectors, etc., which are known to those skilled in the art. However, other configurations are available to transmit data between the sensor system 12 and the data acquisition equipment 18.

Referring additionally now to FIG. 2, an example is representatively illustrated of a sensor system 20 which may be used in the method 10. The sensor system 20 includes a tubular structure 22 in which strain is induced by a pressure differential and temperature change in the well. The strain is detected by strain sensors 24, 26.

Temperature change induces strain in the structure 22 in the sense that temperature change causes a dimensional change which is detected as a strain in the structure by the strain sensors 24, 26.

As depicted in FIG. 2, the structure 22 is preferably a closed-end hollow cylinder, whose length is at least several times its outer diameter, and whose wall thickness is relatively thin. In this manner, hoop and axial strain in the structure 22 due to a pressure differential between the interior and exterior surfaces of the structure may be readily calculated using known mathematical relationships, and contributions due to edge effects, discontinuities, etc. are reduced or eliminated. However, it should be clearly understood that principles of the invention may be incorporated into sensor systems in which pressure responsive structures have other shapes, and in which strains have other mathematical relationships to pressure applied to the structure.

For the closed-end tubular structure 22 depicted in FIG. 2, axial strain due to a pressure differential across interior and external surfaces of the structure may be calculated using the following formula:

- 7 -

$$\epsilon_{zz} = \frac{1}{E} \left(\frac{((2\nu - 1)P_i + \nu P_o)r_i^2 - 2\nu P_o r_o^2}{r_i^2 - r_o^2} \right)$$

Hoop strain due to the pressure differential may be calculated using the following formula:

$$5 \quad \epsilon_{\theta\theta} = \frac{1}{E} \left(\frac{((2\nu - 1)P_i - \nu P_o)r_i^2 r^2 - ((\nu - 1)P_o r^2 + (1 + \nu)(P_i - P_o)r_i^2)r_o^2}{r^2(r_o^2 - r_i^2)} \right)$$

It will be readily appreciated that, if the dimensions of the structure 22 are known, appropriate values for Young's modulus (E) and Poisson's ratio (ν) are known for the corresponding structure material, and the axial and hoop strains (ϵ_{zz} , $\epsilon_{\theta\theta}$) are known from the strain sensors 24, 26, then the pressure differential across the structure may be readily calculated using the above mathematical relationships.

If a temperature change in the well occurs, the strains as detected by the strain sensors 24, 26 may vary. Contraction or expansion of the structure 22 induced by the temperature change will be detected as strain in the structure by the strain sensors 24, 26. However, since this contraction or expansion is isotropic in the structure, the same strain contribution due to the temperature change will be detected by each of the strain sensors 24, 26. Therefore, this contribution due to the temperature change may be conveniently mathematically eliminated from the strains detected by the strain sensors 24, 26.

Note that the strain sensors 24, 26 are preferably positioned very close to each other on the structure 22, so that they each sense strain due to the same temperature changes, i.e., they are attached to portions of the structure at the same temperature. It may be preferable to position each of the strain sensors 24, 26 at the same longitudinal distance between opposite ends of the structure 22.

As depicted in FIG. 2, the strain sensor 24 is oriented longitudinally relative to the tubular structure 22 and the strain sensor 26 is oriented circumferentially relative to the structure. The strain sensor 24 is used to detect axial strain in the structure 22 and the strain sensor 26 is used to detect hoop strain in the structure.

The strain sensors 24, 26 are orthogonal relative to each other and are positioned approximately midway between opposite ends of the structure 22. For clarity of illustration in FIG. 2, the sensors 24, 26 are depicted on the same lateral side of the structure 22 and offset longitudinally with respect to each other. However, preferably the sensors 24, 26 are each centered at the same longitudinal position on the structure 22, but offset radially with respect to each other by 180° (i.e., on opposite lateral sides of the structure 22). Of course, strain sensors may be otherwise oriented and otherwise positioned, and may detect strains in other directions, without departing from the principles of the invention.

The strain sensors 24, 26 are depicted in FIG. 2 as being attached to an outer side surface of the structure 22 and positioned in an annular space 28 between the structure and an outer housing 30. Preferably, the annular space 28 is at atmospheric pressure. Pressure in the well is admitted into an interior bore 32 of the structure 22.

Thus, the pressure differential across the structure 22, which causes axial and hoop strain in the strain sensors 24, 26, is the difference between well pressure in the bore 32 and atmospheric pressure in the annulus 28. However, it should be understood that, in other sensor systems incorporating principles of the invention, the pressure differential could be due to other pressures acting on the structure 22 in other ways. For example, the annulus 28 could be at a pressure other than atmospheric pressure, the well pressure could be applied external to the structure 22, etc.

As used herein, the term "well pressure" refers to a pressure to which the sensor system 20 is exposed in a well, and which it is desired to measure. Thus, well pressure may be a pressure in the interior of a wellbore, a pressure from the exterior of the wellbore, pressure in an item of equipment in a well, etc.

Where the strain sensors 24, 26 are fiber optic sensors, a fiber optic line 34 may be used for communication. Either or both of the strain sensors 24, 26 may be an interferometric fiber optic sensor in which reflection or absorption of specific light wavelengths varies depending on the strain experienced by the sensor. For example, the sensor may include a fiber Bragg grating, a pi-shifted

fiber Bragg grating, a long period grating, a co-located fiber Bragg grating and pi-shifted fiber Bragg grating, a fiber Bragg laser, an intrinsic or extrinsic Fabry-Perot interferometer, a Michelson interferometer, a Mach-Zehnder interferometer, a fiber ring resonator, etc. Of course, other types of strain
5 sensors may be used, such as metal foil strain gauges, etc.

Referring additionally now to FIG. 3, a graph 38 is representatively illustrated of reflectivity vs. wavelength for two types of fiber optic strain sensors. A plot 36 for a uniform fiber Bragg grating is shown as a dashed line in the graph 38, and a plot 40 for a pi-shifted fiber Bragg grating is shown as a solid line in the
10 graph.

Note that the uniform fiber Bragg grating plot 36 has a peak 42 in reflectivity at a wavelength of 1550 nm, while the pi-shifted fiber Bragg grating has a peak 44 in transmission (a dip in reflectivity) at that wavelength. As the length of the sensor changes, the wavelength at which the peaks 42, 44 occur
15 changes. Thus, these fiber optic sensors accurately measure strain by reflecting and transmitting certain light wavelengths. The pi-shifted fiber Bragg grating may be preferred over the uniform fiber Bragg grating since its peak 44 is narrower and more well defined.

Referring additionally now to FIG. 4, another sensor system 50 embodying
20 principles of the invention is representatively illustrated. The sensor system 50 includes an outer housing 52 in which two chambers 54, 56 are separated by a membrane 58. As depicted in FIG. 4, the chambers 54, 56 and membrane 58 are integrally formed, but they could instead be formed of various elements and materials.

25 The membrane 58 is illustrated as being circular-shaped and having a uniform wall thickness. However, sensor systems incorporating principles of the invention may include membranes having other shapes and configurations. Preferably, the membrane 58 has a shape and configuration for which a predetermined mathematical relationship exists between strain detected by one
30 strain sensor 60 and strain detected by another strain sensor 62 attached to the membrane.

The strain sensors 60, 62 may be similar to the strain sensors 24, 26 described above. In particular, the strain sensors may be fiber optic strain sensors.

For the membrane 58 of the sensor system 50, the strain sensor 60 is
5 attached centrally on the membrane, and the strain sensor 62 is attached peripherally on the membrane. A mathematical relationship between a pressure differential across opposite sides of the membrane 58 and the strains as detected by the strain sensors 60, 62 may be derived theoretically, using tools, such as finite element analysis or neural networks, or the relationship may be derived
10 empirically or through statistical analysis, etc.

Preferably, the upper chamber 54 exposed to an upper side of the membrane 58 has atmospheric pressure therein. The strain sensors 60, 62 are attached on the upper side of the membrane 58. Well pressure is admitted into the lower chamber 56, where it is in contact with a lower side of the membrane
15 58. Thus, the pressure differential across the membrane 58 is the difference between well pressure and atmospheric pressure on opposite sides of the membrane.

Referring additionally now to FIG. 6, another sensor system 70 embodying principles of the present invention is representatively illustrated. The sensor
20 system 70 includes an outer housing 72 and an inner tubular structure 74 similar in some respects to the sensor system 20 shown in FIG. 2. An annular space 76 is positioned between the structure 74 and the housing 72, and two strain sensors 78, 80 are externally attached to the structure in the annular space.

The strain sensors 78, 80 are preferably fiber optic sensors similar to the
25 sensors 24, 26, 60, 62 described above. In this embodiment, the sensors 78, 80 are wrapped multiple times about the structure 74, so that a larger magnitude of dimensional change (in the circumferential direction) in the structure is detected by each of the sensors as pressures and temperatures acting on the structure change. Of course, the strain sensors 78, 80 may be otherwise attached to the
30 structure 74 in keeping with the principles of the invention. For example, the sensors 78, 80 could be attached to the structure 74 so that they detect axial strain, etc.

The structure 74 is tubular only in a lower portion 82 thereof. An upper portion 84 of the structure 74 is solid. Fluid pressure is admitted into the structure 74 via an opening 85 into the interior of the tubular lower portion 82. A differential between pressure in the annular space 76 and the fluid pressure admitted into the opening 85 acts only across the lower tubular portion 82 of the structure 74. The upper strain sensor 78, thus, does not detect strain induced in the structure 74 by the pressure differential.

Instead, the upper strain sensor 78 detects strain in the structure 74 induced only by temperature change. The lower strain sensor 80 detects strain induced both by the pressure differential and by the temperature change. The strain induced by the temperature change in the structure 74 is preferably detected the same by each of the strain sensors 78, 80 (for example, by using the same type of strain sensor for both of the sensors 78, 80, mounting the sensors similarly on the structure, etc.). Therefore, the strain in the structure 74 due only to the pressure differential may be readily determined by finding the difference between the strains detected by the sensors (i.e., strain detected by lower strain sensor 80 – strain detected by upper strain sensor 78 = strain due to pressure differential).

A predetermined relationship between the pressure differential and the strain due to the pressure differential (e.g., the mathematical relationships described above) may then be used to calculate the pressure differential. However, it should be understood that sensor systems incorporating principles of the invention may be differently configured so that strain sensors thereof detect other strains in a structure.

Of course, a person skilled in the art would, upon a careful consideration of the above description of representative embodiments of the invention, readily appreciate that many modifications, additions, substitutions, deletions, and other changes may be made to the specific embodiments, and such changes are contemplated by the principles of the present invention. Accordingly, the foregoing detailed description is to be clearly understood as being given by way of illustration and example only, the spirit and scope of the present invention being limited solely by the appended claims and their equivalents.

WHAT IS CLAIMED IS:

1. A subterranean well sensor system, comprising:
a structure in which strain is induced in response to a pressure differential
5 in the well; and
first and second strain sensors attached to the structure and detecting strain in the structure when the pressure differential exists in the well, the first strain sensor detecting a first strain in a first direction in the structure, and the second strain sensor detecting a second strain in a second direction in the
10 structure.
2. The sensor system according to Claim 1, wherein a predetermined mathematical relationship exists between the pressure differential, the first strain and the second strain.
15
3. The sensor system according to Claim 1, wherein strain is induced in the structure in response to a change in temperature in the well, and wherein at least one of the first and second strains includes strain induced in the structure due to the temperature change.
20
4. The sensor system according to Claim 3, wherein each of the first and second strains includes strain induced in the structure due to the temperature change.
- 25 5. The sensor system according to Claim 1, wherein each of the first and second strains includes strain induced in the structure due to the pressure differential.

- 13 -

6. The sensor system according to Claim 1, wherein only one of the first and second strains includes strain induced in the structure due to the pressure differential.

5 7. The sensor system according to Claim 1, wherein the structure includes a hollow cylinder, and wherein the first strain sensor detects axial strain in the cylinder and the second strain sensor detects hoop strain in the cylinder induced by the pressure differential.

10 8. The sensor system according to Claim 7, wherein the first and second strain sensors are each centered at approximately a same longitudinal position on the cylinder, and the first and second sensors are radially offset with respect to each other by approximately 180°.

15 9. The sensor system according to Claim 7, wherein each of the first and second strain sensors detects strain in the cylinder induced by a temperature change in the well.

20 10. The sensor system according to Claim 9, wherein each of the first and second strains includes strain induced in the cylinder by the pressure differential and by the temperature change.

25 11. The sensor system according to Claim 10, wherein a predetermined mathematical relationship exists between the pressure differential and the first and second strains, so that the pressure differential may be calculated when the first and second strains are known.

12. The sensor system according to Claim 7, wherein the pressure differential exists between an interior and an exterior of the cylinder.

13. The sensor system according to Claim 12, wherein well pressure is applied to the interior of the cylinder and approximately atmospheric pressure is applied to the exterior of the cylinder.

5 14. The sensor system according to Claim 1, wherein the structure includes a pressure responsive membrane, and wherein each of the first and second strain sensors detects strain in the membrane induced by the pressure differential.

10 15. The sensor system according to Claim 14, wherein each of the first and second strain sensors detects strain in the membrane induced by a temperature change in the well.

15 16. The sensor system according to Claim 15, wherein each of the first and second strains includes strain induced in the cylinder by the pressure differential and by the temperature change.

20 17. The sensor system according to Claim 16, wherein a predetermined mathematical relationship exists between the pressure differential and the first and second strains, so that the pressure differential may be calculated when the first and second strains are known.

25 18. The sensor system according to Claim 14, wherein the pressure differential exists between opposite sides of the membrane.

19. The sensor system according to Claim 18, wherein well pressure is applied to one side of the membrane and approximately atmospheric pressure is applied to the other side of the membrane.

20. The sensor system according to Claim 1, wherein the structure includes first and second portions, and wherein the first strain sensor detects strain in the first portion and the second strain sensor detects strain in the second portion.

5

21. The sensor system according to Claim 20, wherein the pressure differential induces strain in the first portion, but the pressure differential does not induce strain in the second portion.

10

22. The sensor system according to Claim 20, wherein each of the first and second strain sensors detects strain in the structure induced by a temperature change in the well.

15

23. The sensor system according to Claim 22, wherein the first strain includes strain induced in the structure by the pressure differential and by the temperature change, but the second strain does not include strain induced in the structure by the pressure differential.

20

24. The sensor system according to Claim 23, wherein a predetermined mathematical relationship exists between the pressure differential and the first and second strains, so that the pressure differential may be calculated when the first and second strains are known.

25

25. The sensor system according to Claim 20, wherein the pressure differential exists between an interior and an exterior of the structure.

26. The sensor system according to Claim 25, wherein well pressure is applied to the interior of the structure and approximately atmospheric pressure is applied to the exterior of the structure.

30

27. The sensor system according to Claim 1, wherein at least one of the first and second strain sensors is a fiber optic sensor.

28. The sensor system according to Claim 27, wherein the fiber optic
5 sensor is an interferometric fiber optic sensor.

29. The sensor system according to Claim 27, wherein the fiber optic sensor comprises a fiber Bragg grating.

10 30. The sensor system according to Claim 27, wherein the fiber optic sensor comprises a pi-shifted fiber Bragg grating.

31. The sensor system according to Claim 27, wherein the fiber optic sensor comprises a long period grating.

15

32. The sensor system according to Claim 27, wherein the fiber optic sensor comprises a fiber Bragg laser.

20 33. The sensor system according to Claim 27, wherein the fiber optic sensor comprises a selected one of an intrinsic and extrinsic Fabry-Perot interferometer.

34. The sensor system according to Claim 27, wherein the fiber optic sensor comprises a Michelson interferometer.

25

35. The sensor system according to Claim 27, wherein the fiber optic sensor comprises a Mach-Zehnder interferometer.

- 17 -

36. The sensor system according to Claim 27, wherein the fiber optic sensor comprises a co-located fiber Bragg grating and pi-shifted fiber Bragg grating.

5 37. The sensor system according to Claim 27, wherein the fiber optic sensor comprises a fiber ring resonator.

38. A subterranean well sensor system, comprising:

a generally tubular structure having a pressure differential applied across its inner and outer surfaces, the pressure differential existing between well pressure applied to one of the inner and outer surfaces and a second
5 predetermined pressure applied to the other of the inner and outer surfaces; and

first and second strain sensors, each of the first and second strain sensors detecting strain in the structure induced by the pressure differential and strain induced in the structure by a temperature change in the well, the first strain sensor detecting strain in the structure in a first direction, and the second strain
10 sensor detecting strain in the structure in a second direction different from the first direction.

39. The sensor system according to Claim 38, wherein the structure includes a hollow cylinder, wherein the first strain sensor detects axial strain in
15 the cylinder, and wherein the second strain sensor detects hoop strain in the cylinder.

40. The sensor system according to Claim 39, wherein the first and second strain sensors are each centered at approximately a same longitudinal
20 position on the cylinder, and the first and second sensors are radially offset with respect to each other by approximately 180°.

41. The sensor system according to Claim 38, wherein the second predetermined pressure is contained within an annular space between the
25 structure and an outer housing.

42. The sensor system according to Claim 41, wherein the first and second strain sensors are positioned in the annular space and are attached to the outer surface of the structure.

43. The sensor system according to Claim 38, wherein the second predetermined pressure is approximately atmospheric pressure.

5 44. The sensor system according to Claim 38, wherein at least one of the first and second strain sensors is a fiber optic sensor.

45. The sensor system according to Claim 44, wherein the fiber optic sensor is an interferometric fiber optic sensor.

10 46. The sensor system according to Claim 44, wherein the fiber optic sensor comprises a fiber Bragg grating.

47. The sensor system according to Claim 44, wherein the fiber optic sensor comprises a pi-shifted fiber Bragg grating.

15

48. The sensor system according to Claim 44, wherein the fiber optic sensor comprises a long period grating.

20 49. The sensor system according to Claim 44, wherein the fiber optic sensor comprises a fiber Bragg laser.

50. The sensor system according to Claim 44, wherein the fiber optic sensor comprises a selected one of an intrinsic and extrinsic Fabry-Perot interferometer.

25

51. The sensor system according to Claim 44, wherein the fiber optic sensor comprises a Michelson interferometer.

52. The sensor system according to Claim 44, wherein the fiber optic sensor comprises a Mach-Zehnder interferometer.

53. The sensor system according to Claim 44, wherein the fiber optic
5 sensor comprises a co-located fiber Bragg grating and pi-shifted fiber Bragg grating.

54. The sensor system according to Claim 44, wherein the fiber optic sensor comprises a fiber ring resonator.

55. A subterranean well sensor system, comprising:

a structure having a pressure differential applied across a membrane of the structure, the pressure differential existing between well pressure applied to a first side of the membrane and a second predetermined pressure applied to a second side of the membrane; and

first and second strain sensors, each of the first and second strain sensors detecting strain in the membrane induced by the pressure differential and strain induced in the membrane by a temperature change in the well, the first strain sensor detecting strain in the membrane in a first direction, and the second strain sensor detecting strain in the membrane in a second direction different from the first direction.

56. The sensor system according to Claim 55, wherein the first and second directions are orthogonal to each other.

57. The sensor system according to Claim 55, wherein the first strain sensor is positioned centrally on the membrane, and wherein the second strain sensor is positioned peripherally on the membrane.

58. The sensor system according to Claim 55, wherein the second predetermined pressure is approximately atmospheric pressure.

59. The sensor system according to Claim 55, wherein at least one of the first and second strain sensors is a fiber optic sensor.

60. The sensor system according to Claim 59, wherein the fiber optic sensor is an interferometric fiber optic sensor.

61. The sensor system according to Claim 59, wherein the fiber optic sensor comprises a fiber Bragg grating.

5 62. The sensor system according to Claim 59, wherein the fiber optic sensor comprises a pi-shifted fiber Bragg grating.

63. The sensor system according to Claim 59, wherein the fiber optic sensor comprises a long period grating.

10 64. The sensor system according to Claim 59, wherein the fiber optic sensor comprises a fiber Bragg laser.

15 65. The sensor system according to Claim 59, wherein the fiber optic sensor comprises a selected one of an intrinsic and extrinsic Fabry-Perot interferometer.

66. The sensor system according to Claim 59, wherein the fiber optic sensor comprises a Michelson interferometer.

20 67. The sensor system according to Claim 59, wherein the fiber optic sensor comprises a Mach-Zehnder interferometer.

25 68. The sensor system according to Claim 59, wherein the fiber optic sensor comprises a co-located fiber Bragg grating and pi-shifted fiber Bragg grating.

69. The sensor system according to Claim 59, wherein the fiber optic sensor comprises a fiber ring resonator.

70. A subterranean well sensor system, comprising:

a structure having first and second portions, a pressure differential applied across the first portion, the pressure differential existing between well pressure applied to a first surface of the first portion and a second predetermined pressure applied to a second surface of the first portion; and

first and second strain sensors, each of the first and second strain sensors detecting strain in the structure induced by a temperature change in the well, the first strain sensor detecting strain in the first portion induced by the pressure differential, and the second strain sensor detecting strain in the second portion induced by the temperature change but not detecting strain in the second portion induced by the pressure differential.

71. The sensor system according to Claim 70, wherein the structure first portion is generally tubular and the structure second portion is substantially solid.

72. The sensor system according to Claim 70, wherein the second predetermined pressure is contained within an annular space between the structure and an outer housing.

20

73. The sensor system according to Claim 72, wherein the first and second strain sensors are positioned in the annular space.

74. The sensor system according to Claim 70, wherein the second predetermined pressure is approximately atmospheric pressure.

25

75. The sensor system according to Claim 70, wherein at least one of the first and second strain sensors is a fiber optic sensor.

76. The sensor system according to Claim 75, wherein the fiber optic sensor is an interferometric fiber optic sensor.

77. The sensor system according to Claim 75, wherein the fiber optic
5 sensor comprises a fiber Bragg grating.

78. The sensor system according to Claim 75, wherein the fiber optic sensor comprises a pi-shifted fiber Bragg grating.

10 79. The sensor system according to Claim 75, wherein the fiber optic sensor comprises a long period grating.

80. The sensor system according to Claim 75, wherein the fiber optic sensor comprises a fiber Bragg laser.

15

81. The sensor system according to Claim 75, wherein the fiber optic sensor comprises a selected one of an intrinsic and extrinsic Fabry-Perot interferometer.

20 82. The sensor system according to Claim 75, wherein the fiber optic sensor comprises a Michelson interferometer.

83. The sensor system according to Claim 75, wherein the fiber optic sensor comprises a Mach-Zehnder interferometer.

25

84. The sensor system according to Claim 75, wherein the fiber optic sensor comprises a co-located fiber Bragg grating and pi-shifted fiber Bragg grating.

85. The sensor system according to Claim 75, wherein the fiber optic sensor comprises a fiber ring resonator.

86. A method of measuring pressure in a subterranean well, the method comprising the steps of:

applying a pressure differential across a structure positioned in the well;

5 detecting a first strain in the structure in a first direction using a first strain sensor;

detecting a second strain different from the first strain in the structure in a second direction using a second strain sensor; and

calculating the pressure differential using a predetermined mathematical relationship between the pressure differential and the first and second strains.

10

87. The method according to Claim 86, further comprising the step of applying a change in temperature to the structure in the well, and

wherein each of the first and second strains includes strain induced by the temperature change.

15

88. The method according to Claim 87, wherein each of the first and second strains includes the same strain induced by the temperature change.

89. The method according to Claim 87, wherein the calculating step
20 further comprises subtracting strain induced by the temperature change from the first and second strains.

90. The method according to Claim 86, wherein in the first and second strain detecting steps, the first and second directions are orthogonal to each
25 other.

91. The method according to Claim 86, wherein in the pressure differential applying step, the structure includes a generally tubular portion and

the pressure differential is applied between inner and outer surfaces of the tubular portion.

92. The method according to Claim 91, wherein in the first strain
5 detecting step, the first strain is an axial strain in the tubular portion, and

wherein in the second strain detecting step, the second strain is a hoop strain in the tubular portion.

93. The method according to Claim 86, wherein in the pressure
10 differential applying step, the structure includes a membrane and the pressure differential is applied between opposite sides of the membrane.

94. The method according to Claim 86, wherein in the first and second
strain detecting steps, at least one of the first and second strain sensors is a fiber
15 optic sensor.

95. A method of measuring pressure in a subterranean well, the method comprising the steps of:

applying a pressure differential across a structure positioned in the well;

applying a temperature change to the structure in the well;

5 detecting a first strain in the structure induced by the pressure differential and the temperature change using a first strain sensor;

detecting a second strain in the structure induced by the temperature change using a second strain sensor, the second strain sensor not detecting strain induced in the structure by the pressure differential; and

10 a predetermined mathematical relationship existing between the pressure differential and the first and second strains.

96. The method according to Claim 95, wherein the difference between the first and second strains is the strain in the structure induced by the pressure differential.
15

97. The method according to Claim 95, wherein in the first strain detecting step, the first strain sensor is attached to a generally tubular portion of the structure.

20

98. The method according to Claim 95, wherein in the second strain detecting step, the second strain sensor is attached to a generally solid portion of the structure.

25 99. The method according to Claim 98, wherein in the pressure differential applying step, the pressure differential is not applied across the solid portion of the structure.

100. A method of measuring pressure in a subterranean well, the method comprising the steps of:

applying a pressure differential across a structure positioned in the well;

applying a temperature change to the structure in the well;

5 detecting a first strain in the structure induced by the pressure differential and the temperature change using a first strain sensor;

detecting a second strain different from the first strain in the structure induced by the pressure differential and the temperature change using a second strain sensor; and

10 a predetermined mathematical relationship existing between the pressure differential and the first and second strains.

101. The method according to Claim 100, wherein each of the first and second strains includes the same strain induced by the temperature change.

15

102. The method according to Claim 100, wherein in the first strain detecting step, the first strain sensor is attached to a generally tubular portion of the structure.

20 103. The method according to Claim 102, wherein in the second strain detecting step, the second strain sensor is attached to the tubular portion of the structure.

25 104. The method according to Claim 103, wherein the first and second strain sensors are each centered at approximately a same longitudinal position on the tubular portion, and the first and second sensors are radially offset with respect to each other by approximately 180°.

105. The method according to Claim 103, wherein in the first and second strain detecting steps, the first strain sensor senses hoop strain in the tubular portion and the second strain sensor senses axial strain in the tubular portion.

THIS PAGE BLANK (USPTO)




FIG. 1

2/4




FIG. 4




FIG. 2

THIS PAGE BLANK (USPTO)




FIG.3

THIS PAGE BLANK (USPTO)

4/4




FIG. 6




FIG. 5

THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 02/23272

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 E21B47/06 G01L19/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 E21B G01L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 320 039 A (ANADRILL INT SA) 14 June 1989 (1989-06-14) See abstract page 5, line 39 - line 56; claims 1,3; figure 1 ---	1,2,5,7, 8,12,86, 90-92
A	US 4 893 505 A (MARSDEN MICHAEL J ET AL) 16 January 1990 (1990-01-16) See abstract column 1, line 35 - line 48; claim 1 ---	1,38,55, 70,86, 95,100
A	US 5 925 879 A (HAY ARTHUR D) 20 July 1999 (1999-07-20) See abstract figure 1 ---	1,38,55, 70,86, 95,100
	--- -/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

8 document member of the same patent family

Date of the actual completion of the international search

28 April 2003

Date of mailing of the international search report

12/05/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Dantine, P

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 02/23272

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 4 366 714 A (ADORNI NAPOLEONE) 4 January 1983 (1983-01-04)</p> <p>See abstract</p>	<p>1,38,55, 70,86, 95,100</p>
A	<p>-----</p> <p>KERSEY A D ET AL: "FIBER-OPTIC SYSTEMS FOR RESERVOIR MONITORING AN ARRAY OF FIBER-OPTIC SENSORS AND FORMATS, INCLUDING FIBER BRAGG GRATINGS, ISHELPING SMARTWELL DESIGNS BECOME EVEN SMARTER" WORLD OIL, GULF PUBLISHING CO. HOUSTON, US, vol. 220, no. 10, October 1999 (1999-10), pages 91-93,96-97, XP000880352 ISSN: 0043-8790 See whole document</p>	<p>1,38,55, 70,86, 95,100</p>
A	<p>-----</p> <p>US 4 738 140 A (KEMPF BURKHARD) 19 April 1988 (1988-04-19)</p> <p>claim 1; figure 2</p>	<p>1,38,55, 70,86, 95,100</p>
A	<p>-----</p> <p>DE 198 07 891 A (ABB RESEARCH LTD) 26 August 1999 (1999-08-26)</p> <p>claim 1</p> <p>-----</p>	<p>1,38,55, 70,86, 95,100</p>

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 02/23272

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0320039	A	14-06-1989	US 4805449 A CA 1311370 A1 DE 3875325 D1 DE 3875325 T2 EP 0320039 A1 NO 884838 A ,B,	21-02-1989 15-12-1992 19-11-1992 11-03-1993 14-06-1989 02-06-1989
US 4893505	A	16-01-1990	NONE	
US 5925879	A	20-07-1999	AU 7293198 A WO 9850673 A1	27-11-1998 12-11-1998
US 4366714	A	04-01-1983	IT 1121122 B DE 3000110 A1 FR 2445951 A1 JP 55110926 A	26-03-1986 24-07-1980 01-08-1980 27-08-1980
US 4738140	A	19-04-1988	DE 3665935 D1 EP 0210523 A1 ES 2000727 A6 JP 63016202 A YU 101686 A1	02-11-1989 04-02-1987 16-03-1988 23-01-1988 31-08-1990
DE 19807891	A	26-08-1999	DE 19807891 A1 AU 1746999 A BR 9908236 A WO 9944023 A1 EP 1060372 A1 NO 20003406 A	26-08-1999 15-09-1999 31-10-2000 02-09-1999 20-12-2000 22-08-2000

THIS PAGE BLANK (USPTO)